



LIVE...RACE...WIN

Hyper 270cc Torsion All Years

	Left Front	Right Front	Left Rear	Right Rear
Bar Size	3/4 x .670	3/4 x .670	3/4 x .730	3/4 x .740
If your car has 7/8 Bars	7/8 x .675	7/8 x .675	7/8 x .725	7/8 x .750
Block Size	1-1/2"	1-1/2"	1-3/4"	1-3/4"
# of Turns Off Block	+1	+0	0	0
Monotube ARS Shocks	326 H2/1	3261/2	3265/2	3263
Monotube Adjustable	E326 5-0.5/1	E326 5-0.5/1	B3268-1/2	B337 3.5/4.5-2 WXS
Twin Tube Shocks	1061	106.5/1	1065/2	1063
Twin Tube Adjustable	E1065-0.5/1	E1065-0.5/1	B1068-2/2	BRC1166-3
Right Side Tire Offset		5/8" to the Right		13"
Tire Pressure	6 psi	6-8 psi	3-8 psi	5-10 psi
Tires: Hoosier	57x6 RD12	57x6 RD12	59-8 or a 61-8 RD12	65 RD12
Tires American Racer	18x6 SD33	18x6 SD33	19x8 SD33	20.0 or 20.5x10 SD33
Wheels	10x6	10x6	10x8 (5" outer)	10x10 (6" or 7" outer)
Stagger	4"-8" (5-1/2" Start)			
Rear Panhard	6-1/2"			
Front Panhard	3-1/4"			

Setup notes:

- Make sure your car is setup according to the setup manual, axles square, offset, chain aligned.
- For a driver heavier than 220 pounds use .775 RR Bar, also keep the seat down as low as possible
- Light weight drivers or a really smooth slick track can run two .730's in back.
- An ARS bump rubber is recommended on the left rear shock
- If the car is bottoming out, add 1/2 to 1 turns on both rear bars and make sure you have a bump rubber on the LR
- On adjustable LR shock, run it 2 turns out from full stiff on normal track, 1 turn out on wet track and 3 turns out on a slick track too much tie down will make the car hoop through the turn, too little tie down makes car unpredictable
- If the car is not turning in right, a slight push when you first point the car in, add more RF weight by taking a 1/2 turn out of the LF and RR and adding a 1/2 turn to RF and LR.
- Tire preparation, grinding, grooving, and siping are essential to getting the most traction, see setup manual
- Add LR RF weight to tighten up on exit, add LF RR weight to tighten up entry
- Add LR RF weight to loosen up on entry, add LF RR weight to loosen up on exit
- Add corner weights by adding 1/2 or taking out 1/2 turn to each corner, ex: add RF LR weight by adding 1/2 turn to LR RF and -1/2 turn to LF RR

To make car tighter

- Move wing back
- Go to 4-1/2" stagger or as little as 4", put on a 61", stretch LR tire is necessary
- Stiffer front bars .690 LF .690 RF
- Reduce LR tie down (-3 from full stiff on a 8-2/1) to tighten up on entry
- Two easy up shocks in front, make RR shock is full soft (if using a 6-3), if using dbl adj go to full tie down (soft comp, stiff rebound)
- Lower rear tire pressures to 4 LR and 5 RR
- To make car tighter coming out (forward bite) raise ride heights front and rear, generally done on a smaller track
- To make car tighter in the middle, lower ride height, just beware of car bottoming out, generally done on 1/3 mile tracks
- Lower rear panhard bar

To make the car looser

- Move wing front, but keep angle at 22 degrees
- Add more stagger (go to a 59" LR) this will achieve 5-1/2" to 8-1/2"
- Stiffen up RR shock, stiffen up rebound on the LF shock, increase rebound in LR shock (note warning above)
- Increase RR tire pressure
- To make car looser coming out lower ride heights, take one to three turns out of each front side and one to two turns out of each rear



LIVE...RACE...WIN

Hyper 270cc Torsion All Years

- Move RR out as far out as it will go, if car is rolling up on RR too much, an extra 1" can be achieved by going to a 7 on 3 RR wheel
- Raise rear panhard bar to as high as 8"
- Soften up front bars, stiffen up rear bars (.630 LF, .630 RF, .750 LR, .775 RR)